
 <p>Port of Fujairah ميناء الفجيرة Port of Fujairah United Arab Emirates</p>	<b>FUJAIRAH OIL TANKER TERMINALS</b>		
	<b>Quality, Health, Safety, Environment and Security Management System</b>		
	Document Title:	<b>PRE-ARRIVAL QUESTIONNAIRE</b>	Revision No.:
Document No.:	<b>FOTT / IMS 014 / OPS / 006 / F02</b>	Revision Date:	15 May 2017

<b>Vessel Name / previous name(s) and date(s) of change:</b>	
<b>IMO Number/ Call Sign</b>	
<b>Port of Registry / IACS Class</b>	
<b>Year of Built</b>	
<b>Type of Tanker: SBT/ IMO 1/IMO 2/IMO 3</b>	
<b>LOA / Extreme breadth (m)</b>	
<b>Parallel Body Length (Ballast/Tropical Loaded Condition)</b>	
<b>Draught:</b> Summer/Tropical Arrival Draught (Fwd/Mid/Aft) Maximum trim expected during operations Departure Draught (Fwd/Mid/Aft)	
<b>Tonnage:</b> NRT GRT	
<b>Displacement (MT):</b> Light Loaded Arrival Departure	
<b>Dead Weight (MT):</b> Summer Tropical	
<b>Manifolds:</b> Size (mm/inch) / Number Distance between center of manifolds (m) Height of centre of manifold from the save all/drip tray grating Height of centre of manifold above waterline (Ballast/Loaded) Extreme height of the centre of manifold above waterline (During operations) Distance inboard from manifold to ship's side/rail Distance bow to manifold & manifold to stern (BCM/SCM in use)	
Terminal loading arm connection is as per "ASME B 16.5 STANDARD ANSI # 150", please confirm suitability with ship's manifold	<input type="checkbox"/> Yes <input type="checkbox"/> No
Confirm Inert gas system fitted	<input type="checkbox"/> Yes <input type="checkbox"/> No
COT's are in inert condition and Inert gas system is fully operational	<input type="checkbox"/> Yes <input type="checkbox"/> No

 <p>Port of Fujairah ميناء الفجيرة Port of Fujairah United Arab Emirates</p>	<b>FUJAIRAH OIL TANKER TERMINALS</b>		
	<b>Quality, Health, Safety, Environment and Security Management System</b>		
	Document Title:	<b>PRE-ARRIVAL QUESTIONNAIRE</b>	Revision No.: 0
	Document No.:	<b>FOTT / IMS 014 / OPS / 006 / F02</b>	Revision Date: 15 May 2017

Vessel Condition: Ballast /Loaded / Part Loaded	
If Loaded, type and quantity of cargo on board in MT/CBM	
Type and quantity of cargo to be discharged/ loaded in MT/CBM -Discharge -Load	
Is the ship intended to load / discharge multi grades? -Grade -Quantity	
Toxic Component which exceeds the international allowed Thresholds: -Flash Point -Stowed cargo temperature (Multi level/Average) -Hydrogen Sulphide (In vapor phase/PPM)	
Is High H2S tanks purged adequately to lower the content within TWA limit	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
Arrival cargo tank pressure (mm/Wg)	
Maximum Load/ Discharge capacity in cubic meter/hour/line	
Maximum acceptable pressure at ship's Manifolds (Bar)	
Is Crude Oil Washing Operation planned at the berth, if so, pre-arrival checklist has been satisfactorily completed.	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
Mooring type, size and number and the SWL: (mm/MT) -Forward -Main Deck -Aft	
Details and deficiencies in the ship's mooring arrangement that could affect the safety of mooring	
Any defects of hull, machinery or equipment that could adversely affect safe operations or delay commencement of cargo handling.	
Specify the area with protrusion / projection off the ship's hull	
Last SIRE inspection: -Date / Issuing Authority	
Last PSC inspection: -Date/ Place / MOU	
Security Level	
Last Port of Call	
Next Port of Call	